

NEW CAPABILITY **3/4" & M20 DIAMETERS!**

Tramec Hill Fastener now has an expanded Cold Forming diameter & length range: #10 - 3/4" diameter up to 7" in length; M5 - M20 diameter up to 177mm in length.



- Wide Array of Head Styles Available
- High Quality Products
- Standards
- Blanks
- Short Lead Time
- Specials per Print
- Proudly Made in the USA!

TRAMEC HILL FASTENER manufactures specialty cold formed, externally threaded fasteners and related products at our plant in Rock Falls, IL. Our 48,000 square foot facility, founded in 1957, has been producing close-tolerance, cold-formed products for decades. We have on-site engineering available to quote to your exact specifications. Contact us today to discuss your special fastener needs.



HILLFASTENER.com
sales@hillfastener.com
Toll Free: 800-435-2955
Phone: 815-625-6600
Fax: 815-625-2407

Manufacturing Plant & Sales Office
1602 McNeil Rd.
Rock Falls, IL 61071

TRAMEC LLC - Corporate Offices
30 Davis Street - P.O. aBox 716
Iola, KS 66749

TRAMEC HILL FASTENER BOLT & SCREW STYLES



STEP BOLT

Diameter Range:
 • #10 - 1/2"
 • M5 - M12
 Length Range:
 • 3/8" - 5"
 • 9.5mm - 177mm



TANK BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm




ROUND HEAD FIN-NECK BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



SHORT-NECK CARRIAGE BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



CARRIAGE BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



ROUND HEAD BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



RIB-NECK CARRIAGE BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



T-HEAD BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



PROJECTION WELD STUD

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



PIPE BOLT

Diameter Range:
 • #10 - 1/2"
 • M5 - M12
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



TRUSS-HEAD SCREW

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



PLOW BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



WHEEL BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



12-POINT FLANGE SCREW

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 5"
 • 9.5mm - 177mm



SQUARE-HEAD BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 5"
 • 9.5mm - 177mm



SERRATED HEX FLANGE SCREW

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



INDENTED HEX FLANGE SCREW

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



HEX WASHER HEAD SCREW

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



HEX HEAD RIB-NECK BOLT

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



HEX CAP SCREW

Diameter Range:
 • #10 - 3/4"
 • M5 - M20
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



SOLID RIVET

Diameter Range:
 • 5/32" - 3/4"
 • 4mm - 20 mm
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



SHOULDER RIVET

Diameter Range:
 • 5/32" - 3/4"
 • 4mm - 20 mm
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



SOLID PIN

Diameter Range:
 • 5/32" - 3/4"
 • 4mm - 20 mm
 Length Range:
 • 3/8" - 7"
 • 9.5mm - 177mm



DOUBLED-ENDED STUD

Diameter Range:
 • #10 - 5/8"
 • M5 - M16
 Length Range:
 • 1" - 7"
 • 25.4mm - 177mm